Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be			U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1318, 0073						
consulted for specific requirements.  IDENTITY (As Used on Label and List)				OMB No. 1218-0072  Note: Blank spaces are not permitted. If any item is not applicable, or no					
Chrome Color Plating Pen PL-1009						space must be ma			
Section I					,	•			
Manufacturer's Name				Emergency Telepho	one Number				
Hunter Products, Inc. Address (Number, Street, City, State, and Zip Code)				(908) 526-8440					
792 Partridge Drive, P.O. Box 6795				Telephone Number for Information (908) 526-8440 Date Prepared					
Bridgewater, NJ 08807	01/02/11 Signature of Preparer (optional)								
				Oignature or rispan	. с. (орислал)				
Section II – Hazardous In	gredients/lde	entity Int	ormation			Other Limits	s		
Hazardous Components (Specific Chemical Identity: Common Name(s))			n Name(s))					% (optional)	
Cobalt Sulfate				0.1mg/m <sup>3</sup>	N.A.			21%	
Nickel Sulfamate				1mg/m³ (Ni)	0.1mg/m <sup>3</sup>			9%	
Citric Acid				N.A.	N.A.			15.5%	
Aqua Pura				N.A.	N.A.			54.5%	
•									
Section III – Physical/Che Boiling Point	tion III – Physical/Chemical Characteristics								
DUILITY FULL	emical Chara	cteristic	s		o0 = 1)				
	emical Chara	cteristic ≈ 212°F	s	Specific Gravity (H <sub>2</sub>	<sub>2</sub> 0 = 1)		N.A.		
Vapor Pressure (mm Hg.)	emical Chara		s	Specific Gravity (H <sub>2</sub> Melting Point	0 = 1)		N.A.		
Vapor Pressure (mm Hg.) Vapor Density (AIR = 1)	emical Chara	≈ 212°F	s	Specific Gravity (H <sub>2</sub>	0 = 1)				
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water	emical Chara	≈ 212°F N.A.	s	Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate	00 = 1)		N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co  Appearance and Odor	mplete	≈ 212°F N.A. N.A.	S	Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate	0 = 1)		N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co  Appearance and Odor	mplete lorless and colorl	≈ 212°F N.A. N.A.	s	Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate	00 = 1)		N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV – Fire and Exp  Flash Point (Method Used)	mplete lorless and colorl	≈ 212°F N.A. N.A.	S Flammable Li	Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)		LEL N.A.	N.A.	EL N.A.	
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV - Fire and Exp Flash Point (Method Used)  Extinguishing Media	mplete lorless and colorl	≈ 212°F N.A. N.A.		Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)			N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV - Fire and Exp Flash Point (Method Used)  Extinguishing Media	implete lorless and colorlo losion Hazar N.A.	≈ 212°F N.A. N.A.		Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)			N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV – Fire and Exp Flash Point (Method Used)  Extinguishing Media  Special Fire Fighting Procedures	mplete lorless and colorle losion Hazar N.A. N.A. N.A.	≈ 212°F N.A. N.A.		Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)			N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV - Fire and Exp Flash Point (Method Used)  Extinguishing Media	mplete lorless and colorle losion Hazar N.A. N.A. N.A.	≈ 212°F N.A. N.A.		Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)			N.A.		
Vapor Pressure (mm Hg.)  Vapor Density (AIR = 1)  Solubility in Water  Co Appearance and Odor  Od  Section IV – Fire and Exp Flash Point (Method Used)  Extinguishing Media  Special Fire Fighting Procedures	mplete lorless and colorle losion Hazar N.A. N.A. N.A.	≈ 212°F N.A. N.A.		Specific Gravity (H <sub>2</sub> Melting Point  Evaporation Rate (Butyl Acetate = 1)			N.A.		

Section V - Reac	tivity Data								
Stability	Unstable			Conditions	to Avoid	_			
	Stable					Exposu	ire to high	temperature.	
Incompatibility (Materia	ls to Avoid)		X						
Hazardous Decomposi	tion or Byproduc	te S	Strong oxidiz	zers. (Acids)					
			I.,A.						
Hazardous Polymerization	May Occur			Conditions	to Avoid	N.A.			
	Will Not Occur		Х						
Section VI – Heal	th Hazard Da	nta							
Route(s) of Entry:		Inhalation? N.A.			Skin? X			Ingestion?	
Health Hazards (Acute	and Chronic)				^			^	
		Mildly caus	tic.						
Carcinogenicity:		NTP?		IARC Monographs?			OSHA Regulated?		
		N.A.			N.A.			N.A.	
Signs and Symptoms of	of Exposure	NAILal la coma inc		:f:td F					
		IVIIIa burnin	g sensation	ir ingested. F	ossible mild ras	sn upon pro	ongea ski	in exposure.	
Medical Conditions		NI A							
Generally Aggravated	by Exposure	N.A.							
Emergency and First A	id Procedures								
3-4 glasses of water or	milk.	For skin co	ntact, wash	with soap an	d water. For eye	e contact, f	lush thorou	ughly with water. If ingested, dilute with	
guide et al.									
Section VII - Pred	cautions for	Safe Hand	dling and	l Use					
Steps to Be Taken in C	Case Material is R	Released or S	Spilled		241				
		Use standa	rd clean-up	procedures v	vith water.				
Maria Diagraph Maria	.1								
Waste Disposal Metho	a 	Dispose in	accordance	with local re	gulations.				
Precautions to Be Take	en in Handling an		ol. drv locat	ion. Avoid acc	cidental ingestio	on or skin o	r eve conta	act.	
					- U		•		
Other Precautions		N.A.							
		IV.A.							
Section VII - Con	trol Measure	:S							
Respiratory Protection	(Specify Type)	NI A							
Ventilation		N.A.	Local Exha				Special		
Moderate ventilation.				N.A			0.1	N.A.	
			Mechanica		erate ventilation	n.	Other	N.A.	
Protective Gloves		(	Optional		Eye Protection	n	Optio	onal	
Other Protective Clothi	ng or Equipment		I.A.						
Work/Hygienic Practice	es			after use and	d before eating	or smoking			
		V	vasii nanus	Page		or sillokilly		U.S.G.P.O.: 1986-491-529/45775	